

FSM U Series Under Counter refrigeration units combine high performance with convenience. All units come with quality refrigeration components, easy clean interiors, easy to use digital controller, castors, magnetic door closure and large handles.

UNDER COUNTER REFRIGERATION - Stainless steel door

Features include:

- ▶ High density polyurethane foam insulation.
- ▶ Stainless Steel exterior and interior.
- ▶ Magnetic closing doors with large ergonomic handles
- ▶ Fan cooling system.
- ▶ Auto-defrosting and digital controller.
- ▶ Self-evaporating drainage system.
- ▶ Door gaskets are easily replaceable.
- ▶ Unit comes with PVC coated shelves.
- ▶ Internal round corner edges for easy cleaning.
- ▶ GD Models are equipped with interior lighting and heated mullions.
- ▶ Chiller temp range: +2°C to +5°C. 404A Refrigerant.
- ▶ Ambient temperature rated 36°C (32°C for glass doors).
- ▶ Supplied on 100mm dia. castors.
- ▶ Corded with 10amp plug.



Due to continuous product development, specifications and appearance may differ slightly

| MODEL | DIMENSIONS EXTERNAL (mm) | DIMENSIONS INTERNAL (mm) | GROSS VOLUME (L) | REFRIGERANT | TEMP RANGE °C | COMPRESSOR | VOLTAGE/ AMPS | NET WT (Kgs) | GROSS WT (Kgs) | TEMP CONTROL | No. SHELVES | \$ |
|-----------|--------------------------|--------------------------|------------------|-------------|---------------|------------|---------------|--------------|----------------|--------------|-------------|------|
| UCB1575SD | 1500 x 760 x 840 | 1045 x 635 x 584 | 385 | R404A 340g | +1 to +5 | 1/6HP | 240V 3.5A | 98 | 128 | DIGITAL | 4 | 3200 |

Special*

\$1,800+GST

*whilst stocks last. Subject to availability and FSM standard T&CS. Delivery to Melbourne Metro only